



## CARBOPOMP / M IIT

Mandrel built hose for delivery of petrol, diesel oil, biodiesel to engine on private boats up to 24 mt. The composition of the materials allows to have a hose thinner than the standard ones and guarantees a good resistance to bends, kinking and permeations of the different kinds of fuels. Complying **SAE J 1527:2004 USCG -A1 R1 - ISO 7840:2004-A1-CE 0474 R.I.NA – LLOYD'S REGISTER**

### 5 YEARS GUARANTEE



Black smooth synthetic rubber suitable for petroleum products up to 50% aromatic content, biodiesel, ecological fuel with max. 15% oxygenated compound.




High tensile textile plies








Black smooth self-extinguishing synthetic rubber resistant to abrasion, heat, oil, ozone and marine environment. Fabric impression



Red :  ITALY – CARBOPOMP MARINE FUEL SAE J1527:2004 USCG TYPE A1 R1-ISO 7840:2004 A1 CE 0474 RINA – LLOYD'S REGISTER

 SAE J 1527:2004 A1 R1 – ISO 7840:2004 A1 CE Ø/year embossed

 mm	 mm	 Kg/mt	 Kpa	 Bar
20	31	0.700	35	> 10
25	37	0.860	35	> 10
30	42	0.995	-	> 10
32	44	1.050	-	> 10
35	47	1.130	-	> 10
38	52	1.400	-	> 10
40	54	1.480	-	> 10
45	59	1.650	-	> 10
48	62	1.720	-	> 10
50	64	1.800	-	> 10
57	71	1.980	-	> 10
60	74	2.080	-	> 10

Other sizes and / or pressures on request