

## **Semi Flexible Solar panel OS20-18MFX**

We can produce the flexible solar panel size and the junction box location by customers' request. Pls do not hesitate to let us know if you have special idea for the semi flexible solar panel.

This 20W semi flexible solar panel can be widely used on yacht, boat, RV roof and so on. Our 2<sup>nd</sup> generation newest product main advantage is higher efficient in producing power, more light in weight and more water proof and durable in long use.

### **1. Mechanical Data:**

- 1).Flexible Angle : up to 10 degree
- 2).Back Sheet: PET or fiberglass (PCB)
- 3).J-Box: IP 67 rated
- 4).Thickness of ETFE: 0.025mm
- 5).Thickness of solar panel: 2.5mm or 3mm
- 6).Cables/Connector: 1.5 meter 2\*0.75mm<sup>2</sup> cable with MC4 connectors
- 7).Type of Solar Cells: Monocrystalline silicon cells
- 8).Eyelets: 4pcs in the corners
- 9).By pass diode: 2pcs (10A in one piece)

### **2. Electrical Data:**

1).Peak Power(Pmax)-----	20W
2).Maximum Power Voltage (Vmp)-----	18V
3).Maximum Power Current (Imp)-----	1.11A
4).Open Circuit Voltage (Voc)-----	21.24V
5).Short Circuit Current (Isc)-----	1.22A
6).Maximum System Voltage-----	DC 500V
7).Voltage Tolerance-----	+5%-3%
8).Power Tolerance-----	±3%
9).Number of Cells-----	36pcs
10).Operating Temperature-----	-20°C~+50°C
11).Storage Temperature-----	-20°C~+30°C
12).Temperature Coefficients of Isc(%)-----	+0.09%/ <sup>°</sup> C
13).Temperature Coefficients of Pmax(%)-----	-0.37%/ <sup>°</sup> C
14).Temperature Coefficients of Voc(%)-----	-0.34%/ <sup>°</sup> C

**(Test Condition: AM=1.5, E=1000W/m<sup>2</sup> , Tc=25°C)**

### **3. Flexible Solar Panel Size&Packing Information:**

Solar Panel Size (1pc)-----	600*300*2.5mm
Carton Size(5pcs)-----	670*370*230mm
Net Weight (1pc)-----	0.85kgs
Q'ty/ctn-----	5pcs
Gross Weight (5pcs)-----	10.5kgs

## Semi Flexible Solar panel OS20-18MFX

---

### 4. Product Structure:

