

User's Manual

MR2080W

**MP3-COMPATIBLE
MARINE CD RECEIVER**

RDS MODEL WITH
SWITCHABLE
USA/EUROPEAN FREQUENCIES

BOSS
marine



BOSS
marine

MR2080W
MP3-COMPATIBLE CD RECEIVER
01.2007

tech support: www.bossaudio.com/support

iPod is a trademark of Apple Computer, Inc.,
registered in the U.S. and other countries.



BOSS
AUDIO SYSTEMS
BOSS Audio Systems • 3451 Lunar Court • Oxnard, CA 93030
www.bossaudio.com
800.999.1236

BOSS
AUDIO SYSTEMS



MR2080W RDS Model with
Switchable USA/European
Frequencies
Fully Marinized
MP3-Compatible CD Receiver

**Congratulations on your
purchase of a BOSS Marine
MP3/CD Receiver.**

It has been designed, engineered
and manufactured to bring you
the highest level of performance
and quality, and will afford you
years of listening pleasure.

Thank you for making
BOSS Marine your choice for
marine audio entertainment!

USER'S MANUAL

page	CONTENTS
2	Head unit installation
6	Remote control installation <i>Flush mount</i>
6	Remote control installation <i>Surface mount</i>
10	General and tuner controls
14	Remote control
15	CD Playback
15	MP3 playback
16	RDS radio functions
17	PTY station categories
18	Wiring diagram
19	Troubleshooting
20	Specifications

MR2080W Marine MP3/CD Receiver Packing List

Before installing your new BOSS CD Receiver, please unpack the contents and check that your package contains the following items:

Main unit

Mounting hardware for main unit:

Mounting brackets (2) with adhesive tape

Mounting sheet (paper with hole markings)

Mounting screws, M4 x 30mm (4)

Rubber sealing gasket

Rear mounting bracket

Plain washer

Spring washer

Screw, M5 x 25mm

Hex nut

Wiring harness

Wired remote control

Remote control cable

Mounting hardware for remote control:

Mounting arms (2)

Mounting tube (1)

Machine screws (2)

User's manual

Warranty card

Head unit installation

Before installing your new **BOSS** AUDIO SYSTEMS CD Receiver, please become familiar with all the information contained in this manual.

Choose a mounting location where the unit will not distract or otherwise interfere with the pilot's ability to control the boat.

Use only the installation parts and hardware provided with the unit to ensure proper installation. Using other parts can cause malfunction and possible damage to your **BOSS** AUDIO SYSTEMS CD receiver.

Do not install this unit at an angle in excess of 30° from horizontal, as it may affect performance.


Although this unit has been designed for outdoor use, you can extend its life if you install it in a location which is not subject to extreme temperatures, from such sources as heaters or exhaust lines. Also, if you see dirt, dust or debris on a disc or in the CD slot, remove it with a clean cloth to avoid pushing it into the player mechanism.

To remove dirt from the faceplate, use a clean cloth lightly moistened with filtered water. If the unit is splashed with water, wipe it off with such a clean damp cloth before the water has dried to avoid an accumulation of salts on the face of the unit.


If properly installed, this unit will meet the IPX5 Waterproof standard. Please note that this does NOT mean the unit is submersible, but will resist being sprayed and splashed as might occur in a normal boat cabin.

To ensure that the installation meets the IPX5 Waterproof Standard, please follow these steps carefully.

1. Remove the transport screws from the top of the enclosure before beginning the installation.




2. Examine the mounting sheet included with the unit. Decide on the location you wish to put the unit, and stick this sheet to the dash there.




Stick mounting sheet to dashboard in mounting location

Head unit installation, continued


3. Using a sharp knife, saw or other appropriate tools as may be required, cut out the rectangular shape specified on the mounting sheet. Then drill the four 3/16" (5mm) mounting holes in the EXACT locations shown on the mounting sheet.




4. Using the double-faced adhesive paper provided, stick the mounting brackets in place behind the opening. ***Before you press them firmly in place, be certain that the holes in the bracket are visible through the holes you made in the dashboard!***



5. Carefully pop off the plastic mounting screw covers from the faceplate to reveal the four mounting holes. Use a small, flat-bladed screwdriver for this purpose.




5. Slide the rubber sealing gasket from the back of the unit until it is snug against the rear surface of the faceplate.



Head unit installation, continued


6. Insert and tighten the support screw into the back of the head unit where shown.



PLEASE NOTE: If your installation is such that once you install the head unit into the dashboard you will NOT have access to the audio and power connectors or cables, make all your connections at this time.

7. Mount the unit in place using the four M4 x 30mm screws provided. These screws go through the front panel, then the mounting places, then dashboard, and finally engage in the mounting brackets.


Tighten them securely and then snap the mounting screw covers back in place.



Head unit installation, continued

8. Insert the head unit into the dashboard. Inspect the dashboard material to determine its approximate thickness.

Bend the backstrap to conform to the mounting case and the dashboard surface to which you plan to secure the backstrap. Slide one of the utility holes on the backstrap onto the support screw and fasten it with the spring washer and nut provided.



Remote control installation

The **BOSS** AUDIO SYSTEMS Marine Remote Commander has been designed with particular attention to ease and flexibility in installation.


It can be mounted in both flush-mount and surface mount situations. Both use our exclusive “push and turn” system. In both types of mountings, you will first attach the mounting cup in place.

Once the cup is secure, you simply feed the wires thru the hole in the back of the cup (flush mount) or the lower edge of the cup (surface mount) and then insert and turn the remote until it is engaged.

FLUSH MOUNT


Follow these steps for a successful installation:

1. Select the proper location which accommodates the 3.45” overall diameter, and mark its centerpoint.
2. Drill a hole with diameter of 3.2”-3.3” (82-84mm). **It is very important that the hole does not exceed 3.3”.**
3. Place the O-ring provided in the groove on the rear surface of the flange of the mounting cup.




Place O-ring in groove on rear surface of flange of cup.

4. Insert mounting arms fully into mounting tube.




5. Insert mounting screws provided through the slots in the cup and into the threaded holes in the mounting arms. Do not tighten more than a few turns.

Insert the mounting screws through the cup into the threaded holes in the mounting arms



6. Insert this assembly fully into the hole you have cut so that the flange rests on the mounting surface.

Be sure the cup is oriented with arrow next to the word TOP is pointing UP or your remote will be turned when it is installed!




Insert the cup assembly fully into the hole you have cut.

Remote control installation, continued

7. Using your fingers, grasp the heads of the mounting screws and slide them out, away from the center of the cup. This will cause the mounting arms to also slide out so that when you tighten the screws, the ends of the arms will be engaged behind the mounting panel.


Slide the screws out to extend the mounting arms so that they reach behind the mounting surface.




8. Tighten the screws equally until the cup is firmly seated and the O-ring is contacting the mounting surface.

Please note: With the mounting arms installed as shown ("pointing to the front"), this mounting system can be used on mounting surfaces up to about 3/4". For thicker surfaces, you can reverse the arms, which will permit mounting to surfaces about 1" thick.

9. Press the cable into the curved groove on the back of the remote housing. Feed the cable end thru the relief hole at the back of the cup.




10. Hold the remote in front of the cup with the top up, and as you hold it, rotate it about 20° counterclockwise.




11. Insert the remote control fully into the cup so that the mounting hooks penetrate the slots in the back of the cup.

If you feel resistance when you insert the remote into the cup, pull the remote housing and check that the cable has been pressed into the curved slot, as described in Step 2).



12. Grasp and turn the remote to the right until it is in the correct position.



Remote control installation


SURFACE MOUNT

Follow these steps for a successful installation:

1. Place the mounting cup in the location you wish to install it.

Be sure the cup is oriented with arrow next to the word TOP is pointing UP or your remote will be turned when it is installed!


Using screws of suitable size and type for your application, attach the cup to the mounting surface. If necessary, drill pilot holes for the screws first.




2. If you are going to run the cable into a hole in the mounting surface, drill a hole of at least 9/16" (15mm) so that you can pass the remote cable connector through it.

If you are going to run the cable out the bottom relief hole and out along the mounting surface, skip this step.

Drill a 9/16" (15mm) or larger hole to allow cable to pass through mounting surface.




3. Press the cable into the curved groove on the back of the remote housing. Feed the cable end thru the relief hole at the BACK of the cup OR the bottom of the cup.



Installation with cable going into hole in mounting surface.

- OR -




Installation with cable running out on top of mounting surface.

Remote control installation, continued


3. Hold the remote in front of the cup with the top up, and as you hold it, rotate it about 20° counterclockwise.

Hold the remote in front of the cup, turned about 20° counterclockwise.




4. Insert the remote control fully into the cup so that the mounting hooks go through the slots in the back of the cup.

If your installation is one in which the cable is exiting out the bottom of the housing (NOT the back), as you insert the remote module pull the cable down gently so it does not interfere with the insertion of the remote into the cup.




If you feel resistance when you insert the remote into the cup, pull the remote housing out and check that the cable has been pressed into the curved slot, as described in Step 2).

5. Grasp and turn the remote to the right until it is in the correct position.



General and Tuner Controls



1 POWER

Press this button to turn unit on. Press POWER again to turn it off.

2 MODE (Input Select)

Press this button repeatedly to cycle through the audio input sources in the following order:

RADIO > CD > AUX IN > AUX1 (front panel aux input)

To clear all stored memories, press and hold this button for several seconds.

3 TUNE/TRACK BUTTONS

In Radio mode, press these buttons briefly to step up or down the radio dial in single step increments. Press and hold for more than one-half second and the tuner will enter the SEEK mode. In this mode the tuner will stop at the next strong station available.

In CD mode, pressing these buttons briefly will advance the player to the next (or previous) track. Press and hold and the player will enter SEARCH mode.

4 DISC DOOR

This door features a waterproof seal to prevent water from entering the unit. To open it, press down on the latch to release it. The door can then drop down. To eject a disc, you must first open the door. It is recommended that you keep it closed except when changing or removing discs.

5 MO/ST, AF (Alternate Frequency)

If you are dissatisfied with the quality of the reception in stereo, switching to mono often improves the overall sound quality. To do this, press this button briefly.

Press and hold this button to turn on the RDS AF function, which compares the signal strength of the current station with others on the same network and changes to improve reception. See page 16 for more information.

6 EJECT

To eject a disc, you must first open the door. Then press this button and the disc mechanism will move the disc out to where you can grab it and remove it safely.

7 VOLUME UP/DOWN BUTTONS

In normal operation, these buttons are used to increase or decrease the volume level.

Used in combination with the SELECT button, these buttons are used to increase or decrease the settings of various audio parameters.

8 SELECT

The SELECT button is used to access a wide range of settings for the receiver.

AUDIO SETTINGS

To change settings in the audio section, press SELECT briefly, repeatedly, to step thru the following audio parameters:

VOLUME > BASS > TREBLE > BALANCE > FADER

Use the UP/DOWN buttons to change the settings as desired. If you have made a change to a setting, press SELECT to enter it and move to next parameter. When you are finished making settings, after about 5 seconds the unit will return to normal mode.

Please note: If you have selected a preset EQ curve, the settings for BASS and TREBLE will not be available in the Audio Settings section.

SYSTEM SETTINGS

General Settings

To access system setup items, press and hold SELECT for more than two seconds.

The LCD will display "MENU" and then will display the first adjustable item, which is "CLOCK."

Press SELECT briefly to step thru the available settings. Use the UP/DOWN buttons to make any changes. The following list shows the sequence of items in the menu, and the choices possible. **The factory default is indicated in bold type.**

- **Clock 12HR/24HR:** 12HR or 24HR In areas with US frequencies **12 HR**, in areas with European frequencies, **24HR**.

- **CT (Clock time):** If the frequency area switches from American to European, the clock will display 24:00. Similarly if the area switches from European to American, the clock will display 12:00. Use the UP/DOWN buttons to adjust the minutes or hours.

- **Subwoofer channel:** **ON/OFF**

- **LOC/DX radio reception:** LOC/**DX**

- **Area:** Factory set to **the country in which the radio is sold**. Europe > Latin > OIRT > AUST > ASIA > USA

- **V-PGM (maximum volume level):** 0-**12**

- **Beep (when you press a button):** **ON/OFF**

- **Clock On (determines if clock will be displayed when radio is turned off):** **ON/OFF**

- **LCD1/2 (LCD brightness level):** 1/**2**

RDS Radio Settings

• SEEK RDS/ALL

This setting determines the behavior of the radio SEEK function when RDS tuning mode. If ALL is selected, the SEEK function will stop at both RDS and non-RDS stations. Otherwise, it will only seek RDS stations. **RDS/ALL**

• TA (Traffic Alert) SEEK/ALARM

When TA mode is on, the radio monitors the Public Information channel which is piggy-backed on the FM channel you are currently enjoying. If such a channel is not detected or is weak the tuner will SEEK another PI channel and monitor it. (This is the TA SEEK setting).

If ALARM setting is chosen, if a signal is insufficiently strong, instead of monitoring an alternate station for PI information, the radio will produce a double beep (alarm) and silence itself, and display "LOST TP TA." **TA SEEK/ALARM**

• TA VOLUME

This setting determines the volume level of the Traffic Alerts as they play. 0-40 (**18 is default**)


• REG ON/OFF

This setting determines the behavior of the radio reception when AF (Alternate Frequency) mode is on. The AF system continuously monitors the signal strength of a station and compares it with other stations on the same network. If another station is stronger, it changes to that station.

Since sometimes in different regions stations on the same network will play different programs, the AF system can interrupt the current program. If REG ON is selected, the station will check if the programs are the same, and if not, the TA system will not change the station.

REG OFF/ON

General and Tuner Controls, continued



9 LOUDNESS/TA

Press briefly increase the level of bass output. Press again to turn off the Loudness function.

Press a little longer to turn on the TA (Traffic Alert) mode. For more information about this mode, please see page 16 of this manual)

10 AUX IN JACK

This jack is a convenient way to play music from an MP3 music player such as an iPod through your marine stereo.

Simply connect the headphone output of the MP3 player to this input jack, and use the CD Receiver's MODE button to select AUX as input source and begin playing music on the MP3 player.

11 DISPLAY (Clock display and setting)

Press this button briefly to display the current time. To reset the time, press and hold this button until it begins flashing. Then you can use the UP/DOWN buttons to change the hour and minutes.

12 PRESETS 1-6 (Radio Mode)

These buttons are used to store the presets for radio stations. To set a preset, tune to the desired radio station. Then press and hold the preset to which you wish to assign that station for more than one second and release. To replace it with a different station, repeat the process and the new setting will override the previous one.

12a +10/-10 (next/previous 10 tracks)

These button are used during disc playback to skip ahead or back ten tracks.

12b REPEAT

In CD Playback Mode, when you press this button briefly, the player will keep repeating the same track until you press it again.

In MP3/WMA Playback Mode, when you press this button, the player will keep repeating the same track until you press it again. Press and hold this button to repeat all the tracks in the current folder.

12c RANDOM

In CD Playback Mode, pressing this button will cause the player to play all the songs on the current disc in random order.

In MP3/WMA Playback Mode, press and hold this button and the player will play all the songs in the current folder in random order.

In both modes, press RANDOM again to cancel the Random playback mode.

12d **INTRO SCAN**

The Intro Scan function is a convenient way to find a particular track.

In CD Playback Mode, press this button and the player will play the first few seconds of a song, and then skip to the next song and play a few seconds of that song. This process continues until you press the INTRO button again, and the player will continue playing that song.

In MP3/WMA Playback Mode, press and hold this button and the player will play the first few seconds of a song in the current folder, and then skip to the next song and play a few seconds of that song. This process continues until you press the INTRO button again, and the player will continue playing that song.

13 **EQ (Preset Equalizer Curves) PTY (RDS Program Type Tuning)**

Press briefly, repeatedly to cycle through five modes: POP > JAM > JAZZ > ROCK > CLASSICAL > FLAT > OFF.

Press and hold this button to turn on the PTY function and begin RDS tuning radio stations. For information on assigning using the PTY function, please see page 17 of this manual.

14 **BAND**

Press briefly, repeatedly to cycle between the radio bands:

FM1 > FM2 > FM3 > AM1 > AM2

15 **PLAY/PAUSE, MUTE**

In CD mode, discs will begin playback automatically upon insertion. To pause playback, press this button. Press again to resume playback.

In Radio, AUX and AUX 1 modes,

Press this button to silence the audio. Press again to restore the previous audio volume level.

16 **SCAN, EON ON/OFF**

In Radio mode, when you press this button briefly the tuner will scan up the band until it detects a strong station. Then it will stop, and the frequency of that station will be displayed in a flashing pattern for about 5 seconds. If you wish to hear this station, press SCAN again. If you do not push SCAN, the tuner will scan up to the next station and repeat the same pattern.

To turn on EON mode of RDS System, press and hold this button. When the EON function is turned on, "EON" will be displayed on the screen (for more information about the EON function see page 16).

17 **AS/PS (Automatic preset setup, preset scan function)**

When pressed and held for several seconds, the tuner will search and store the first six strong stations as presets in the current radio band.

Press this button briefly, repeatedly to step between and listen to the six presets of the current band.

Remote Control

1 POWER

Use to turn CD Receiver ON or OFF.

2 MODE

Press to choose desired audio source:
RADIO > CD > AUX IN > AUX 1 (front panel aux input)

3 BAND

Press briefly, repeatedly to cycle between the radio bands:

FM1 > FM2 > FM3 > AM1 > AM2

4 SCAN/EON ON/OFF


In Radio Mode, when you press this button briefly the tuner will scan up the band until it detects a strong station. Then it will stop, and the frequency of that station will be displayed in a flashing pattern for about 5 seconds. If you wish to hear this station, press SCAN again. If you do not push SCAN, the tuner will scan up to the next station and repeat the same pattern.

To turn on EON mode of RDS System, press and hold this button. When the EON function is turned on, "EON" will be displayed on the screen (for more information about the EON function see page 16).

5 TUNE/TRACK (◀ and ▶)

In Radio Mode, press and release to activate automatic seek function ("AUTO" will appear on display). Press and hold to engage manual tuning mode ("MANUL" will appear on display).

In CD Mode, press and release to advance to the next track or to return to the beginning of the current track (track number will be displayed). Press and hold to fast forward or reverse. Play will begin at the point when you release the button.



6 PLAY/PAUSE

Discs will begin playback automatically upon insertion. To pause playback, press this button. Press again to resume playback.

7 VOLUME

Use to increase or decrease volume level.

8 MUTE

In Radio, AUX and AUX 1 modes, Press this button to silence the audio. Press again to restore the previous audio volume level.

Please note: MUTE is not available in CD Playback mode.


CD playback

Please follow these general instructions to play a music CD disc. On the column to the right, you will find instructions for using MP3 discs.

Please note that only some of these functions are available on the remote control.

Loading a disc

Press down the latch on the disc door as shown in the figure below, and then push it down to open the door.



Push down on latch to release it, then push it down to open the door.

Gently insert a disc into the disc slot until you feel it being drawn in by the player mechanism. If there is already a disc in the player, first press EJECT to eject it and remove it.

Playing a disc

The disc will begin playing automatically. If you wish to pause playback, press PLAY/PAUSE, and press again to resume playback.

To start playback from the first track, press PRESET 1. To skip ahead or back ten tracks on the disc, press the +10 or -10 button.

Intro Scan function

The Intro Scan function is a convenient way to find a particular track. Press this button and the player will play the first few seconds of a song, and then skip to the next song and play a few seconds of that song. This process continues until you press the INTRO button again, and the player will continue playing that song.

Repeating a track

To keep repeating the same track, press the REPEAT button. To cancel the repeat function, press again.

Random play

Pressing the RANDOM button will cause the player to play all the songs on the current disc in random order. Press again to cancel this function.

MP3 disc playback

When you insert an MP3 (or WMA) disc, the player will begin playback from the first track in the directory.

However, MP3 discs can contain many more tracks than audio CD's, so you may wish to search for a particular track to play. There are two search methods available.

TRACK SEARCH MODE

In disc playback mode, press the BAND button once. The LCD will display the word "TRACK."

To begin searching, press SELECT or the UP/DOWN button. Then press and hold the UP or DOWN button to locate the desired track, and press SELECT to begin playback.

NAVIGATE THE CURRENT FOLDER

This mode permits you to navigate the file directory present on the disc.

To enter this mode, press BAND twice. The display will display "NAVIGA." Press SELECT to enter this mode.

Use the UP and DOWN buttons to move up and down the directory of folders and files on the disc. To enter a subfolder, highlight it and press SELECT. You will then see the directory of that subfolder and can select tracks within it. So play a track, highlight it and push SELECT.

VIEWING MP3 FILE INFORMATION

Since many MP3 files are tagged with Music/Artist/Album (ID3-TAG) information, you can see this as a list by pressing AS/PS repeatedly.

The information will appear as a scrolling display, including the folder and file name as well as the ID3-TAG information.

Please note that if this information is not present in ID3-TAG version 1.0 or 2.0 format, it will not be displayed.

RDS Radio functions

The RDS (Radio Data System) is a digital information system created by the European Broadcast Union (EBU).

This system “piggy-backs” a variety of information services onto normal FM broadcasts. This information can only be decoded by a radio with RDS decoding, like this model.

The three main RDS functions are described below:

AF/REG (Alternate Frequency)

When this mode is enabled by pressing and holding the MO/ST•AF button, the radio will continuously monitor the signal strength of the broadcast you are listening to and if it finds the same network broadcast on a different frequency which is stronger, it will automatically switch to the stronger signal.

Regional mode setting

In the SELECT menu (see page 11 in this manual) you can choose to turn on or off the REG (regional mode) subfunction within AF mode. **The default mode is OFF.**

Although the AF button can sense if one station on a network is stronger than another, it will not confirm that the actual program being broadcast is the same unless you turn ON the REG mode.

TA (Traffic Announcement)

Many FM stations offer traffic announcements in addition to their regular programming.

If you enable the TA function by pressing the TA button, when this station broadcasts a traffic advisory, the radio's RDS tuner will automatically interrupt the regular program and play the alert. When the alert is finished, normal play of the broadcast will resume.

The TA function will also interrupt CD and MP3 playback temporarily if the EON feature has been enabled (see below).

There are some other settings for TA behavior that you can change. See the SELECT instructions on page 11 for more information.

RDS EON function setting

The RDS EON system extends the functionality of the TA sensing to a wider range of traffic announcements from both local and national sources. It also allows the unit to interrupt disc playback with these announcements. In addition, it will play these announcements (at normal listening level) even if the audio has been muted.

(To set this level, see instructions on page 9 for setting V-PGM level).

To enable the EON function, press and hold the SCAN button. Press again to disable it.

With EON enabled, when a traffic announcement is broadcast, the radio will switch automatically to TA mode, and “TP” (Traffic Program) will be displayed.

PTY (Program type)

A number of RDS stations can be selected by the type of program they broadcast, i.e. news, sport or classical music.

Press and hold the PTY button to cause the tuner to switch to RDS PTY type tuning. If at any time you wish to return to normal tuning mode, press and hold again.

When you have entered PTY mode, the display will show "PTY" indicating that the mode is enabled, and the name of the first program type, "NEWS."

To view other PTY categories, use the UP/DOWN buttons (a list of these categories is shown on the next page). To select the category, highlight it and press SELECT. If there is no station found in that category, the display will show "NONE PTY" and the radio will return to normal mode.

PTY Station Categories


This list shows the PTY program types in the order presented in the radio display:

NEWS
AFFAIRS
INFORMATION
SPORTS
EDUCATION
DRAMA
CULTURE
SCIENCE
VARIETY
POP MUSIC
ROCK MUSIC
EASY LISTENING MUSIC
LIGHT MUSIC
CLASSICAL MUSIC
OTHER MUSIC
WEATHER
FINANCE
CHILDREN
SOCIAL
RELIGIOUS
PHONE IN
TRAVEL
LEISURE
JAZZ MUSIC
COUNTRY MUSIC
NATIONAL MUSIC
OLDIES MUSIC
FOLK MUSIC
DOCUMENTARY
ALERT TEST
ALARM TEST

Wiring diagram

Follow the wiring illustration below closely to obtain proper performance from your CD receiver. Failure to make these connections properly may result in damage to your unit which will not be covered under your warranty.

This receiver contains a built-in high power four-channel amplifier. To use the built-in amplifier, connect the speaker wires as shown. To use the receiver as a head unit in a 2CH, 4CH or 4CH-plus-subwoofer mobile audio system which includes an amplifier(s) or power subwoofer, use the RCA outputs to connect to the RCA inputs of your amplifier(s).



Troubleshooting

If you experience operation or performance problems with this product, compare your installation with the electrical wiring diagram on the previous page. If problems persist, read the following troubleshooting tips which may help eliminate the problems.

SYMPTOM	CAUSE	REMEDY
No power.	The car ignition switch is not on.	<i>If the head unit is properly connected to the car accessory power circuits, but the engine is running, switch the ignition key to the "ACC" position.</i>
	The fuse is blown.	<i>Replace the fuse.</i>
Disc cannot be loaded or ejected.	There is a disc already in the CD player.	<i>Remove disc in player and try again.</i>
	Disc is inserted upside down.	<i>Insert the disc with the label facing up.</i>
	Disc is dirty or defective.	<i>Clean the disc, or play a new one.</i>
	Car interior temperature is too high.	<i>Allow temperature to cool down to a normal level.</i>
	Excess atmospheric humidity or condensation is present.	<i>Leave player off for an hour or so, and then try again.</i>
No sound.	Volume is set to minimum.	<i>Adjust volume to desired level.</i>
	Wiring not properly connected.	<i>Check wiring connections.</i>
Sound skips.	Head unit is installed at an angle of greater than 30° from horizontal.	<i>Adjust installation angle to less than 30° from horizontal.</i>
	Disc is dirty or defective.	<i>Clean the disc, or play a new one.</i>
Buttons on front panel do not operate.	The built-in micro-processor is not operating properly due to noise.	<i>Press the RESET button.</i>
	Front panel is not properly fixed in place.	<i>Remove front panel, press RESET button, and re-insert front panel.</i>
Radio does not work, or the radio automatic selection function does not work.	Antenna cable not connected.	<i>Insert the antenna cable firmly into connector.</i>
	The signals are too weak to be received properly.	<i>Select station manually.</i>

Specifications



MR2080W

Fully-Marinized MP3-Compatible CD Receiver • RDS Model with Switchable USA/European Frequencies

CD PLAYER

Signal-to-noise ratio	Greater than 50dB @ 1kHz
Frequency response	20Hz - 20kHz
Compatible formats	CD, CD-R, CD-RW, MP3, WMA

RADIO

FM Section:

Frequency range	87.5 - 108MHz (EUROPE), 87.5 - 107.9MHz (USA)
Usable sensitivity	3uV
Intermediate frequency	10.7MHz

AM Section:

Frequency range	522 - 1620kHz (EUROPE), 530 - 1710kHz (USA)
Usable sensitivity	40dB
Intermediate frequency	450kHz

AMPLIFIER

Maximum output power	80 watts x 4 channels
----------------------	-----------------------

GENERAL

Power supply req.	12VDC, negative ground
Current consumption	15A Max
Line out voltage	1200mV
Chassis dimensions (W X H X D)	7" x 2" x 6.4" (178 x 50 x 160 mm)

All specifications subject to change without notice.