

NEPTUNA TOURING 15W-40



Mineral oil for 4-stroke Petrol or Diesel engines used for pleasure craft.

APPLICATIONS

**4-stroke engines
Petrol or diesel**

- Fortified technology oil for lubrication of all sorts of petrol or diesel engines, turbocharged or naturally aspirated.
- Recommended for pleasure craft applications under normal utilisation conditions.

PERFORMANCE

**ACEA
API**

**Conforming to the
manufacturer's
requirements**

- Conforming to international specifications:
ACEA E2 / A2 / B2
API CG-4 / SJ

The exclusive formula has been approved by the following manufacturers:

- MAN: 271
- VOLVO: VDS
- MTU: Oil type 1
- BAUDOUIN: SMB 4
- PERKINS, IVECO, DEUTZ,
- NANNI, PETER, YANMAR, TOHATSU ...

CLIENT ADVANTAGES

**Performance
and functioning safety**

- High viscosity stability in use
- Improved detergency
- Excellent anti-wear and anti-corrosion properties, especially in a humid or aggressive atmosphere

CHARACTERISTICS

NEPTUNA TOURING	Units	15W-40
Volumetric mass	kg/m ³	887
Viscosity at 100°C	mm ² /s	14
Viscosity index		132
Pour point	°C	- 30
TBN	mg KOH/g	9.2

The values for the data given in this table are typical values given by way of information only

TOTAL LUBRIFIANTS
16, rue de la République
F- 92800 PUTEAUX
1/1

NEPTUNA TOURING 15W-40
JULY 2005
N°07/05



This lubricant, when used in accordance with our recommendations and for the application for which it is intended does not constitute a special hazard.
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.