


NEPTUNA GEAR SYN 75W-90



A very high performance synthetic oil for pleasure craft outdrives and transmissions.

APPLICATIONS

**Outdrives
Transmissions**

Loaded gears

- Oil specially recommended for loaded gears used in outdrives and transmissions of pleasure craft.
- Also suitable for all transmission systems using gears, bevel gears, stepdown gears, etc.

PERFORMANCE

API GL-5

MIL 2105D

- Meets the most stringent international specifications for gears: API GL-5
- In conformity with MIL 2105 D specification

CLIENT ADVANTAGES

**Operability
in all seasons**

High performance

Safety

- Its exclusive synthetic compound formula confers upon it operability at all temperatures: from the lowest (- 30°C) to the highest (130°C)
- Fortified extreme pressure protection
- Particularly efficient at high temperature and under heavy loads
- Withstands attacks due to marine environment humidity and acidity
- Particularly advance anti-wear and anti-corrosion protection
- No foaming or emulsification when in service.

CHARACTERISTICS

NEPTUNA GEAR SYN	Units	75W-90
Volumetric mass	kg/m ³	884
Viscosity at 40°C	mm ² /s	106
Viscosity at 100°C	mm ² /s	17
Viscosity index		175
Pour point	°C	- 39

The values for the data given in this table are typical values given by way of information only