

## Product Data

## HEMPEL'S PRE-CLEAN 67602

Description:	HEMPEL'S PRE-CLEAN 67602 is a high strength, cleaner and degreaser.
Recommended use:	For pre-cleaning and degreasing gelcoat, painted and varnished surfaces to remove fuel, oil, grease, wax and silicone. Use prior to painting and for deep cleaning.
Availability:	Subject to confirmation.
PHYSICAL CONSTANTS: Colours/Shade nos: Flash point: Specific gravity: pH value: V.O.C.:	Transparent/09990 Non flammable 1.0 kg/litre – 8.3 lbs/US gallon App. 10 undiluted 0 g/litre – 0 lbs/US gallon The physical constants stated are nominal data according to the HEMPEL Group's approved formulas. They are subject to normal manufacturing tolerances and where stated, being standard deviation according to ISO 3534-1.
Surface preparation:	Rinse the surface with fresh water to remove loose dirt
Application method:	Dilute 1 part of HEMPEL'S PRE-CLEAN 67602 with 1-20 parts of fresh water. Use low dilution for more demanding jobs. Apply HEMPEL'S PRE-CLEAN 67602 with a sponge, soft brush, scotch-brite pad or by spraying using lowest possible pressure. After 5-10 minutes rinse with plenty of fresh water until all residues have been removed. Allow surface to dry. If a white film is left on the surface it can be removed with warm water.
Subsequent treatment:	If surface is in good condition and a high gloss is desired apply HEMPEL'S CLEAN & POLISH 69032 or HEMPEL'S CUSTOM MARINE POLISH 67445.
Remarks:	Shake well before use. Do not expose product to alkaline sensitive substrates such as aluminium for a long period, as this would influence the aluminium shine. Do not expose product to frost. The surface temperature should be above 5°C/41°F.
Note:	The information given in the Product Data Sheet is intended for commercial use.
Safety:	Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Material Safety Data Sheets and follow all local or national safety regulations. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment. Apply only in well ventilated areas.
ISSUED BY:	HEMPEL A/S - 6760209990

This Product Data Sheet supersedes those previously issued. For explanations, definitions and scope, see "Explanatory Notes" in the HEMPEL Book. Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.

The Products are supplied and all technical assistance is given subject to HEMPEL's GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise.

Product data are subject to change without notice and become void five years from the date of issue.

