

| ART. NO. | G | A | D | L1 | L2 | L3 | L4 | B.L./KG | KG/100 | PACK |
|----------|-----|----|------|-----|-----|----|----|---------|--------|------|
| 340435 | M4 | 30 | 4,0 | 66 | 35 | 25 | 30 | 750 | 2,1 | 25 |
| 340535 | M5 | 30 | 4,4 | 67 | 35 | 25 | 30 | 900 | 2,6 | 25 |
| 340635 | M6 | 33 | 5,3 | 67 | 35 | 26 | 30 | 1250 | 4,5 | 5 |
| 340650 | M6 | 33 | 5,3 | 84 | 50 | 26 | 30 | 1250 | 5,7 | 5 |
| 340835 | M8 | 33 | 7,1 | 71 | 35 | 26 | 30 | 1750 | 7,2 | 5 |
| 340850 | M8 | 33 | 7,1 | 86 | 50 | 26 | 30 | 1750 | 9,7 | 5 |
| 340880 | M8 | 33 | 7,1 | 116 | 80 | 26 | 45 | 1750 | 11,8 | 5 |
| 348840 | M8 | 50 | 8,0 | 80 | 40 | 30 | 32 | 1750 | 12,4 | 5 |
| 348850 | M8 | 50 | 8,0 | 90 | 50 | 30 | 32 | 1750 | 13,2 | 5 |
| 341045 | M10 | 40 | 10,0 | 95 | 45 | 40 | 40 | 3500 | 18,4 | 5 |
| 341060 | M10 | 40 | 10,0 | 110 | 60 | 40 | 35 | 3500 | 20,4 | 5 |
| 341010 | M10 | 40 | 10,0 | 150 | 100 | 40 | 85 | 3500 | 25,0 | 5 |
| 341280 | M12 | 47 | 10,8 | 122 | 80 | 30 | 85 | 5100 | 29,0 | 5 |

Note: All breakloads are determined by thread

