

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

**1 Identification**

- Product identifier
- Trade name: Epifanes Easy-Flow
- Application of the substance / the mixture  
See our technical datasheet for application of this product.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
W.Heeren & Zoon bv.  
P.O. box 166  
1430 AD Aalsmeer  
Netherlands  
tel.+31 297-360666  
fax.+31 297-342078  
email:info@epifanes.nl
- Information department: Research & Development.
- Emergency telephone number:  
Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)  
Outside US: 703-527-3887

**2 Hazard(s) identification**

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements

- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS02



GHS07



GHS08

- Signal word Danger

(Contd. on page 2)


Safety Data Sheet  
acc. to OSHA HCS


Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Easy-Flow

(Contd. of page 1)

- Hazard-determining components of labeling:  
Naphtha (petroleum), hydrotreated heavy (Note-p)  
Xylene
- Hazard statements  
H226 Flammable liquid and vapor.  
H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H304 May be fatal if swallowed and enters airways.
- Precautionary statements  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Classification system:
- NFPA ratings (scale 0 - 4)  


Health = 0  
Fire = 2  
Reactivity = 0
- HMIS-ratings (scale 0 - 4)  


Health = 0  
Fire = 2  
Reactivity = 0
- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

**3 Composition/information on ingredients**

- Chemical characterization: Mixtures
- Description:  
Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 64742-48-9 EC number: 919-857-5 Index number: 649-327-00-6	Naphtha (petroleum), hydrotreated heavy (Note-p) Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	25-50%
CAS: 15956-58-8 EINECS: 240-085-3	2-ETHYLHEXAAN ZUUR, MANGAAN ZOUT Repr. 2, H361; STOT RE 2, H373 Eye Irrit. 2A, H319	<0.3%

(Contd. on page 3)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Easy-Flow

(Contd. of page 2)

- Additional information:  
For the wording of the listed hazard phrases refer to section 16.

**4 First-aid measures**

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

**5 Fire-fighting measures**

- Extinguishing media
- Suitable extinguishing agents:  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture  
During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

**6 Accidental release measures**

- Personal precautions, protective equipment and emergency procedures  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:  
Prevent seepage into sewage system, workpits and cellars.  
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:

64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	350 mg/m <sup>3</sup>
------------	--	-----------------------

(Contd. on page 4)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Easy-Flow

(Contd. of page 3)

96-29-7	2-butanone oxime	30 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
· PAC-2:		
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	1,800 mg/m <sup>3</sup>
96-29-7	2-butanone oxime	56 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
· PAC-3:		
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	40,000 mg/m <sup>3</sup>
96-29-7	2-butanone oxime	250 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm

**7 Handling and storage**

- Handling:
- Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- Information about protection against explosions and fires:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

**8 Exposure controls/personal protection**

- Additional information about design of technical systems:  
No further data; see item 7.
  - Control parameters
  - Components with limit values that require monitoring at the workplace:  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information:  
The lists that were valid during the creation were used as basis.
  - Exposure controls
  - Personal protective equipment:
  - General protective and hygienic measures:  
Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Easy-Flow

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.

- Breathing equipment:  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.  
Filter AX
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: nitrile rubber;  
recommended glove thickness > 0.45mm. permeability / permeation time: > 480 min. according to EN 374.
- As protection from splashes gloves made of the following materials are suitable:  
chloroprene; glove thickness > 0.7mm, breakthrough time > 60min. according to EN 374.  
nitrile rubber; glove thickness > 0.3 mm, breakthrough time > 60min. volgens EN 374.
- Eye protection:



Tightly sealed goggles

**9 Physical and chemical properties**

- Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Fluid

(Contd. on page 6)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Easy-Flow

(Contd. of page 5)

Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	150 °C (302 °F)
· Flash point:	45 °C (113 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	0.87049 g/cm <sup>3</sup> (7.26424 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	15 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	43.2 %
VOC content:	43.17 %
	VOC content: 375.8 g/l / 3.14 lb/gal
Solids content:	60.4 %
· Other information	No further relevant information available.

**10 Stability and reactivity**

· Reactivity No further relevant information available.

(Contd. on page 7)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Easy-Flow

(Contd. of page 6)

- Chemical stability
- Thermal decomposition / conditions to be avoided:  
No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

**11 Toxicological information**

- Information on toxicological effects
- Acute toxicity:

- LD/LC50 values that are relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy (Note-p)

Oral	LD50	>5,000 mg/kg bw (rat)
Dermal	LD50	>5,000 mg/kg bw (rabbit) ((24h))
Inhalative	LC50	>5,000 mg/m <sup>3</sup> (vapour) (rat) ((8h))

- Primary irritant effect:  
on the skin: No irritant effect.  
on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:  
The product shows the following dangers according to internally approved calculation methods for preparations:

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

136-52-7	cobalt bis(2-ethylhexanoate)	2B
----------	------------------------------	----

- NTP (National Toxicology Program)  
None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)  
None of the ingredients is listed.

**12 Ecological information**

- Toxicity

- Aquatic toxicity:

64742-48-9 Naphtha (petroleum), hydrotreated heavy (Note-p)

ErL (72h)	>1,000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
EL50 (48h)	>1,000 mg/l ((Daphnia magna-OECD 202))
LL50 (96h)	>1,000 mg/l ((Onorhynchus mykiss OECD 203))
EbL50 (72h)	>1,000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
NOELR (72h)	3 mg/l ((Pseudo. subcapitata-biomass-OECD 201)) 100 mg/l ((Pseudo. subcap. growth rate OECD 201))

- Persistence and degradability No further relevant information available.

(Contd. on page 8)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Easy-Flow

(Contd. of page 7)

- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

**13 Disposal considerations**

- Waste treatment methods
- Recommendation:  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

**14 Transport information**

- UN-Number
  - DOT, ADR, IMDG, IATA
  - UN proper shipping name
  - DOT
  - ADR
  - IMDG
  - IATA
  - Transport hazard class(es)
  - DOT
  - Class
  - Label
- |  |                                    |
|--|------------------------------------|
|  | UN1263                             |
|  | CONSUMER COMMODITY, ORM-D<br>Paint |
|  | 1263 PAINT                         |
|  | CONSUMER COMMODITY, ORM-D<br>PAINT |
|  | PAINT                              |
|  | 3 Flammable liquids                |
|  | 3                                  |



(Contd. on page 9)





Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Easy-Flow

(Contd. of page 8)

· ADR	
	
· Class	3 (F1) Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· Remarks:	CERCLA/DOT RQ: 617gal./4786 lbs.
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Easy-Flow

(Contd. of page 9)

· UN "Model Regulation": UN 1263 PAINT, 3, III

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

136-52-7 cobalt bis(2-ethylhexanoate)

112-34-5 2-(2-butoxyethoxy)ethanol

· TSCA (Toxic Substances Control Act):

64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	ACTIVE
------------	--	--------

8001-26-1	Linseed oil	ACTIVE
-----------	-------------	--------

8016-13-5	Extracts and fysical modified derivats in fishoil. It contain mostly the glycerids of C14-18- en C16-22- unsaturated fatty acids. (mixed fish).	ACTIVE
-----------	---	--------

1330-20-7	Xylene	ACTIVE
-----------	--------	--------

22464-99-9	Zirconiumoctoate, 12 % Zr	ACTIVE
------------	---------------------------	--------

68409-80-3	Isomers of fatty acid calcium salts, C6-C19	ACTIVE
------------	---	--------

15956-58-8	2-ETHYLHEXAAN ZUUR, MANGAAN ZOUT	ACTIVE
------------	----------------------------------	--------

136-52-7	cobalt bis(2-ethylhexanoate)	ACTIVE
----------	------------------------------	--------

96-29-7	2-butanone oxime	ACTIVE
---------	------------------	--------

112-34-5	2-(2-butoxyethoxy)ethanol	ACTIVE
----------	---------------------------	--------

· Hazardous Air Pollutants

1330-20-7	Xylene
-----------	--------

15956-58-8	2-ETHYLHEXAAN ZUUR, MANGAAN ZOUT
------------	----------------------------------

136-52-7	cobalt bis(2-ethylhexanoate)
----------	------------------------------

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Easy-Flow

(Contd. of page 10)

· Cancerogenity categories

· EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· TLV (Threshold Limit Value established by ACGIH)	
None of the ingredients is listed.	
· MAK (German Maximum Workplace Concentration)	
96-29-7	2-butanone oxime 2
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

Naphtha (petroleum), hydrotreated heavy (Note-p)  
Xylene

· Hazard statements

H226 Flammable liquid and vapor.  
H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	25-50

· Water hazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 12)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Easy-Flow

(Contd. of page 11)

- Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Contact:
- Date of preparation / last revision 01/12/2021 / 4
- Abbreviations and acronyms:
  - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
  - ICAO: International Civil Aviation Organisation
  - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - DOT: US Department of Transportation
  - IATA: International Air Transport Association
  - ACGIH: American Conference of Governmental Industrial Hygienists
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - NFPA: National Fire Protection Association (USA)
  - HMS: Hazardous Materials Identification System (USA)
  - VOC: Volatile Organic Compounds (USA, EU)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - NIOSH: National Institute for Occupational Safety
  - OSHA: Occupational Safety & Health
  - TLV: Threshold Limit Value
  - PEL: Permissible Exposure Limit
  - REL: Recommended Exposure Limit
  - Flam. Liq. 3: Flammable liquids - Category 3
  - Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A
  - Repr. 2: Reproductive toxicity - Category 2
  - STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
  - STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2
  - Asp. Tox. 1: Aspiration hazard - Category 1
- \* Data compared to the previous version altered.