



## PM68158 - Precision Masking Tape, Extreme

Description	This single sided tape consists of a reinforced, flat Japanese Washi paper carrier coated on one side with a solvent based acrylic adhesive.
Product properties	This tape gives superior, razor sharp paint lines and is easy to remove. It is extra resistant to tearing and it leave no adhesive residues when removed. The UV-resistant acrylic adhesive is formulated to give an excellent adhesion on rough or uneven surfaces. It is UV-resistant up to 120 days (4 months).
Applications	It is a strong multi-task masking tape, used for extra demanding paint-, plastering- or polishing jobs, both in- and outdoors. Examples are automotive after market masking, multiple layer paint jobs where there is no buildup of paint. Very good for use in combination with water based paints. It is not suitable for application on zinc, copper, anodized metals and natural stone (marble). Can be exposed to UV for maximum 120 days, with a residue free removal. For best results, it is always best to remove the tape before the paint has fully dried.
Storage and ageing	2 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
Applying tips	All substrates should be clean and contamination free, and the tape should be applied with pressure.

### TECHNICAL DATA

UV resistant	Yes	
Color	Orange	
Thickness total	0.11 mm	4.331 Mills
Adhesion on SS	5 N/25mm	1.14 Lbs/inch
Tensile strength length	85 N/25mm	19.41 Lbs/inch
Elongation length	8 %	
Temperature performance (short time)	150 °C	302 °F

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information. See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application. The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use. Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

Stokvis Tapes Norway A/S  
Gamle Drammensvei 120  
1363 Høvik

+47 - 67 17 79 00  
www.stokvistapes.no  
info@stokvistapes.no  
An Illinois Tool Works Company

Rev. 1.00      2023-06-07

Page            1 / 1