

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes Woodfinish Gloss
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU21 Consumer uses: Private households / general public / consumers
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC10 Roller application or brushing
- Environmental release category
 - ERC5 Use at industrial site leading to inclusion into/onto article
 - ERC8c Widespread use leading to inclusion into/onto article (indoor)
 - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- Article category AC11 Wood articles
- Application of the substance / the mixture
See our technical datasheet for application of this product.
high gloss varnish alternative
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31-(0)297-360366
email: r&d@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number:
W.Heeren & Zoon bv. tel: +31 297 360678, E-mail: rend@epifanes.nl
Office hours: weekdays from 08:00 to 17:00.
The National Poisons Information Service; dial 111
Solely intended to inform professionals in acute poisoning!

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3

H226 Flammable liquid and vapour.



Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

STOT SE 3

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 1)

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02 GHS07

- Signal word Warning
- Hazard-determining components of labelling:
Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P)
butan-1-ol
Cobalt bis(2-ethylhexanoate)
- Hazard statements
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other
ignition sources. No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face
protection/hearing protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated
clothing. Rinse skin with water [or shower].
P501 Dispose of contents/container in accordance with local/regional/
national/international regulations.
- Additional information:
EUH066 Repeated exposure may cause skin dryness or cracking.
Contains cobalt carboxylate, can cause an allergic reaction.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description:
Resin mixture
Solvent mixture with additives

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 2)

Mixture of synthetic binders, additives and organic solvents

· Dangerous components:		
CAS: 64742-48-9 EC number: 919-857-5 Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P) ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ STOT SE 3, H336	25-50%
CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.: 01-2119491274-35	barium sulphate, natural substance with a Community workplace exposure limit	≤2.5%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	≤2.5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≤1%
CAS: 22464-99-9 EINECS: 245-018-1 Reg.nr.: 01-2119979088-21	Zirconium 2-ethylhexanoate ⚠ Repr. 2, H361d	≤0.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	Cobalt bis(2-ethylhexanoate) ⚠ Repr. 1B, H360F ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Eye Irrit. 2, H319; Skin Sens. 1A, H317	≥0.1-<0.25%
CAS: 140-66-9 EINECS: 205-426-2 Index number: 604-075-00-6 Reg.nr.: 01-2119541687-29	4-(1,1,3,3-tetramethylbutyl)phenol ⚠ Eye Dam. 1, H318 ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10) ⚠ Skin Irrit. 2, H315	≥0.025-<0.25%

· Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 3)

- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

* **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
No further relevant information available.
- 5.3 Advice for firefighters
Protective equipment: Mouth respiratory protective device.

* **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures
Ensure adequate ventilation
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

See Section 13 for disposal information.

(Contd. of page 4)

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles:
Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural	
WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust
34590-94-8 Dipropylene glycol monomethyl ether	
WEL	Long-term value: 308 mg/m ³ , 50 ppm Sk
71-36-3 butan-1-ol	
WEL	Short-term value: 154 mg/m ³ , 50 ppm Sk
136-52-7 Cobalt bis(2-ethylhexanoate)	
WEL	Long-term value: 0.1 mg/m ³ as Co; Carc, Sen
7727-43-7 barium sulphate, natural	
WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust
34590-94-8 Dipropylene glycol monomethyl ether	
WEL	Long-term value: 308 mg/m ³ , 50 ppm Sk
71-36-3 butan-1-ol	
WEL	Short-term value: 154 mg/m ³ , 50 ppm Sk

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 5)

136-52-7 Cobalt bis(2-ethylhexanoate)		
WEL	Long-term value: 0.1 mg/m ³ as Co; Carc, Sen	
· Regulatory information WEL: EH40/2020		
· DNEL (Derived No Effect Level) voor professionals		
64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P)		
Oral	Long-term - systemic effects.	125 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	185 mg/m ³ (General population)
7727-43-7 barium sulphate, natural		
Inhalative	Long-term - local effects.	10 mg/m ³ (Employees)
	Long-term - systemic effects.	10 mg/m ³ (Employees)
34590-94-8 Dipropylene glycol monomethyl ether		
Dermal	Long-term - systemic effects.	65 mg/kg/day (Employees)
Inhalative	Long-term - systemic effects.	310 mg/m ³ (Employees)
71-36-3 butan-1-ol		
Inhalative	Long-term - local effects.	310 mg/m ³ (Employees)
22464-99-9 Zirconium 2-ethylhexanoate		
Dermal	Long-term - systemic effects.	6.49 mg/kg/day (Employees)
Inhalative	Long-term - systemic effects.	32.97 mg/m ³ (Employees)
136-52-7 Cobalt bis(2-ethylhexanoate)		
Inhalative	Long-term - local effects.	0.037 mg/m ³ (General population)
	Long-term - systemic effects.	0.2351 mg/m ³ (Employees)
140-66-9 4-(1,1,3,3-tetramethylbutyl)phenol		
Inhalative	Long-term - systemic effects.	0.8 mg/m ³ (General population)
· DNEL (Derived No Effect Level) for general audience		
64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P)		
Dermal	Long-term - systemic effects.	208 mg/kg bw/day (Employees)
Inhalative	Long-term - systemic effects.	871 mg/m ³ (Employees)
	Long term - systemic effects.	125 mg/kg bw/day (General population)
7727-43-7 barium sulphate, natural		
Oral	Long-term systemic effects.	13,000 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	10 mg/m ³ (General population)
34590-94-8 Dipropylene glycol monomethyl ether		
Oral	Long-term systemic effects.	1.67 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	15 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	37.2 mg/m ³ (General population)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 6)

71-36-3 butan-1-ol		
Oral	Long-term systemic effects.	3.125 mg/kg bw/day (General population)
Dermal	Long-term - local effects.	55 mg/m ³ (General population)
22464-99-9 Zirconium 2-ethylhexanoate		
Oral	Long-term systemic effects.	4.51 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	3.25 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	8.13 mg/m ³ (General population)
136-52-7 Cobalt bis(2-ethylhexanoate)		
Oral	Long-term systemic effects.	0.0558 mg/kg bw/day (General population)
· PNECs		
7727-43-7 barium sulphate, natural		
	Sewage treatment plant	62.2 mg/l (Sewage treatment plant)
	Aquatic compartment.	0.115 mg/l (Freshwater)
	Soil	600.4 mg/kg (Freshwater)
	Soil	207.7 mg/kg (soil)
34590-94-8 Dipropylene glycol monomethyl ether		
	Aquatic compartment.	19 mg/l (Freshwater)
	Aquatic compartment.	1.9 mg/l (Seawater)
	STP	4,168 mg/l (Segmentation, Targeting and Positioning)
	Soil	70.2 mg/kg (Freshwater)
	Intermittent	190 mg/l (Intermittent)
	Soil	2.74 mg/kg (soil)
	Sediment	7.02 mg/kg (Seawater)
71-36-3 butan-1-ol		
	Sewage treatment plant	2,476 mg/l (Sewage treatment plant)
	Aquatic compartment.	0.082 mg/l (Freshwater)
	Aquatic compartment.	0.0082 mg/l (Seawater)
	Soil	0.0178 mg/kg (Seawater)
		0.178 mg/kg (Freshwater)
	Soil	0.015 mg/kg (soil)
136-52-7 Cobalt bis(2-ethylhexanoate)		
	Aquatic compartment.	0.00051 mg/l (Freshwater)
	Aquatic compartment.	0.00236 mg/l (Seawater)
	STP	0.37 mg/l (Segmentation, Targeting and Positioning)
	Soil	9.5 mg/kg (Freshwater)
	Soil	7.9 mg/kg (soil)

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 7)

	Sediment	9.5 mg/kg (Seawater)
140-66-9 4-(1,1,3,3-tetramethylbutyl)phenol		
Oral	Oral	0.00236 g/kg (Oral)
	Aquatic compartment.	0.001 mg/l (Seawater)
	Aquatic compartment.	0.001 mg/l (Seawater)
	Aquatic compartment - sediment in freshwater	4.62 mg/kg sed dw (Freshwater)
	Aquatic compartment - sediment in marine water	1.23 mg/kg sed dw (Seawater)
	STP	0.1 mg/l (Segmentation, Targeting and Positioning)
	Soil	2.3 mg/kg (soil)
	Intermittent	0 mg/l (Intermittent)

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- Respiratory protection:
In case of short or low load, breathing filter device; in the case of intensive or prolonged exposure, use a breathing apparatus independent of the surrounding air. A half-face mask for organic vapours and solvents according to EN140 type A1 or A2 is recommended.
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 8)

- Penetration time of glove material
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Butyl rubber, BR
- As protection from splashes gloves made of the following materials are suitable:
Cloropene; handglove thickness >0.7mm, penetration time >60min. according EN374.
Nitrilrubber; handglove thickness >0.3mm, penetration time >60min. according EN374.
- Eye/face protection



Tightly sealed goggles

- Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Physical state: Fluid
- Colour: According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range: 154 °C (64742-48-9 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic, < 2% aromatics. (Note-P))
- Flammability: Not applicable.
- Lower and upper explosion limit
- Lower: 0.6 Vol %
- Upper: 7 Vol %
- Flash point: 41 °C
- Auto-ignition temperature: Product is not selfigniting.
- Decomposition temperature: Not determined.
- pH: Not determined.
- Viscosity:
- Kinematic viscosity at 20 °C: 55 s (ISO 6 mm)
- Dynamic: Not determined.
- Solubility
- water: Fully miscible.
- Partition coefficient n-octanol/water (log value): Not determined.
- Vapour pressure: Not determined.
- Density and/or relative density
- Density at 20 °C: 0.94 g/cm³ (ISO 2811)

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 9)

· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	240 °C
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	39.0 %
· VOC content:	39.00 %
	VOC content:
	366.6 g/l / 3.06 lb/gal
· Solids content:	61.0 % (SC% 1h 150C)
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 10)

- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity

- LD/LC50 values relevant for classification:

34590-94-8 Dipropylene glycol monomethyl ether

Oral	LD50	5,135 mg/kg bw (rat)
Dermal	LD50	>19,000 mg/kg bw (rab)
	Long-term exposure (8 hours TWA): 50 ppm	308 mg/m ³ (Occupational exposure limits)

71-36-3 butan-1-ol

Oral	LD50	790 mg/kg bw (rat)
Dermal	LD50	3,400 mg/kg bw (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)

136-52-7 Cobalt bis(2-ethylhexanoate)

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50 (Konijn)	5,000 mg/kg (rabbit)

140-66-9 4-(1,1,3,3-tetramethylbutyl)phenol

Oral	LD50	3,210 mg/kg bw (mouse)
------	------	------------------------

- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards

- Endocrine disrupting properties

98-54-4	4-tert-butylphenol	List I, II
140-66-9	4-(1,1,3,3-tetramethylbutyl)phenol	List I

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

136-52-7 Cobalt bis(2-ethylhexanoate)

LC50	0.1-1 mg/l (Fish Acute Toxicity Study)
EC50	0.1-1 mg/l (daphnia magna)
EC50	0.1-1 mg/l (Algae, Growth inhibition test)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss


(Contd. of page 11)


- 12.6 Endocrine disrupting properties
For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- Remark: Harmful to fish
- Additional ecological information:
- General notes:
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents:
Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- 14.1 UN number or ID number
ADR, IMDG, IATA UN1263
- 14.2 UN proper shipping name
ADR 1263 PAINT
IMDG, IATA PAINT
- 14.3 Transport hazard class(es)
ADR

 - Class 3 (F1) Flammable liquids.
 - Label 3

 - IMDG, IATA

 - Class 3 Flammable liquids.
 - Label 3

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 12)

<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	<p>III</p>
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: 	<p>No</p>
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	<p>Warning: Flammable liquids. 30 F-E, S-E A</p>
<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · Transport category · Tunnel restriction code · Remarks: 	<p>3 D/E Packaging <450L: exemption viscous substances according to 2.2.3.1.5 > 450 l: 3 F1, III</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · Remarks: 	<p>> 450 l: 3, III</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 1263 PAINT, 3, III</p>

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
50,000 t

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 13)

- National regulations:
- Technical instructions (air):

Class	Share in %
NK	25-50

- Waterhazard class:
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360F May damage fertility.
H361d Suspected of damaging the unborn child.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
- Department issuing SDS: Research & Development.
- Contact: J.J. van Dijk, tel: +31 297 360678, email: rend@epifanes.nl
- Abbreviations and acronyms:
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids - Category 3
Acute Tox. 4: Acute toxicity - Category 4
Skin Irrit. 2: Skin corrosion/irritation - Category 2
Eye Dam. 1: Serious eye damage/eye irritation - Category 1

(Contd. on page 15)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 18 (replaces version 17)

Revision: 04.02.2022

Trade name: Epifanes Woodfinish Gloss

(Contd. of page 14)

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Repr. 1B: Reproductive toxicity - Category 1B

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.