

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

**1 Identification**

- Product identifier
- Trade name: Epifanes Bilge Paint
- Application of the substance / the mixture  
See our technical datasheet for application of this product.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
W.Heeren & Zoon bv.  
P.O. box 166  
1430 AD Aalsmeer  
Netherlands  
tel.+31 297-360666  
fax.+31 297-342078  
email:info@epifanes.nl
- Information department: Research & Development.
- Emergency telephone number:  
Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)  
Outside US: 703-527-3887

**2 Hazard(s) identification**

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements
- GHS label elements  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS02



GHS07

- Signal word Warning
- Hazard-determining components of labeling:  
Naphtha (petroleum), hydrotreated heavy (Note-p)
- Hazard statements  
H226 Flammable liquid and vapor.  
H336 May cause drowsiness or dizziness.
- Precautionary statements  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Bilge Paint

(Contd. of page 1)

- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 - 4)



Health = 0  
Fire = 2  
Reactivity = 0

- HMIS-ratings (scale 0 - 4)



Health = 0  
Fire = 2  
Reactivity = 0

- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

**3 Composition/information on ingredients**

- Chemical characterization: Mixtures
- Description:  
Resin mixture  
Solvent mixture with pigment additives

- Dangerous components:

CAS: 64742-48-9 EC number: 919-857-5 Index number: 649-327-00-6	Naphtha (petroleum), hydrotreated heavy (Note-p) Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	25-50%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2	titanium dioxide Carc. 2, H351	25-50%

- Additional information:  
For the wording of the listed hazard phrases refer to section 16.

**4 First-aid measures**

- Description of first aid measures
  - General information: Immediately remove any clothing soiled by the product.
- (Contd. on page 3)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Bilge Paint

(Contd. of page 2)

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Seek medical treatment.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

**5 Fire-fighting measures**

- Extinguishing media
- Suitable extinguishing agents:  
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture  
During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- Protective equipment:  
Wear fully protective suit.  
Mouth respiratory protective device.

**6 Accidental release measures**

- Personal precautions, protective equipment and emergency procedures  
Ensure adequate ventilation  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:  
Prevent seepage into sewage system, workpits and cellars.  
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:

64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	350 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m <sup>3</sup>

(Contd. on page 4)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Bilge Paint

(Contd. of page 3)

112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
· PAC-2:		
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	1,800 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m <sup>3</sup>
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
· PAC-3:		
64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	40,000 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m <sup>3</sup>
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>

**7 Handling and storage**

- Handling:
- Precautions for safe handling
  - Keep away from heat and direct sunlight.
  - Ensure good ventilation/exhaustion at the workplace.
  - Prevent formation of aerosols.
- Information about protection against explosions and fires:
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
  - Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities
- Storage:
  - Requirements to be met by storerooms and receptacles:
    - Store only in the original receptacle.
  - Information about storage in one common storage facility: Not required.
  - Further information about storage conditions: Keep receptacle tightly sealed.
  - Specific end use(s) No further relevant information available.

**8 Exposure controls/personal protection**

- Additional information about design of technical systems:
  - No further data; see item 7.

(Contd. on page 5)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Bilge Paint

(Contd. of page 4)

- Control parameters
- Components with limit values that require monitoring at the workplace:  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information:  
The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.
- Breathing equipment:  
Not necessarily with good ventilation, however, use a filter AX when ventilation is inadequate!
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: nitrile rubber;  
recommended glove thickness > 0.45mm. permeability / permeation time: > 480 min. according to EN 374.
- As protection from splashes gloves made of the following materials are suitable:  
chloropene; glove thickness > 0.7mm, breakthrough time > 60min. according to EN 374.  
nitrile rubber; glove thickness > 0.3 mm, breakthrough time > 60min. volgens EN 374.

(Contd. on page 6)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Bilge Paint

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

**9 Physical and chemical properties**

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Fluid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>100 °C (>212 °F)
· Flash point:	>41 °C (>105.8 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C (68 °F):	1 hPa (0.8 mm Hg)
· Density at 20 °C (68 °F):	1.4 g/cm <sup>3</sup> (11.683 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/ water):	
	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	40 s (ISO 6 mm)

(Contd. on page 7)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Bilge Paint

(Contd. of page 6)

- Solvent content:
  - Organic solvents: 27.5 %
  - VOC content: 27.46 %
  - VOC content: 384.4 g/l / 3.21 lb/gal
- Solids content: 72.5 %
- Other information No further relevant information available.

**10 Stability and reactivity**

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

**11 Toxicological information**

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy (Note-p)

Oral	LD50	>5,000 mg/kg bw (rat)
Dermal	LD50	>5,000 mg/kg bw (rabbit) ((24h))
Inhalative	LC50	>5,000 mg/m <sup>3</sup> (vapour) (rat) ((8h))

13463-67-7 titanium dioxide

Oral	LD50	>20,000 mg/kg bw (rat)
Dermal	LD50	>10,000 mg/kg bw (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

- Primary irritant effect:
  - on the skin: No irritant effect.
  - on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

13463-67-7	titanium dioxide	2B
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	3
7631-86-9	silicon dioxide, chemically prepared	3
136-52-7	cobalt bis(2-ethylhexanoate)	2B

(Contd. on page 8)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Bilge Paint

(Contd. of page 7)

14808-60-7	Quartz (SiO <sub>2</sub> )	1
· NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO <sub>2</sub> )	K
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

**12 Ecological information**

· Toxicity

· Aquatic toxicity:

64742-48-9 Naphtha (petroleum), hydrotreated heavy (Note-p)

ErL (72h)	>1,000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
EL50 (48h)	>1,000 mg/l ((Daphnia magna-OECD 202))
LL50 (96h)	>1,000 mg/l ((Onorhynchus mykiss OECD 203))
EbL50 (72h)	>1,000 mg/l (Pseudokirchneriella subcapitata-OECD 201)
NOELR (72h)	3 mg/l ((Pseudo. subcapitata-biomass-OECD 201))
	100 mg/l ((Pseudo. subcap. growth rate OECD 201))

- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

**13 Disposal considerations**

- Waste treatment methods
- Recommendation:  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

**14 Transport information**

- UN-Number
- DOT, IATA UN1263

(Contd. on page 9)





Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Bilge Paint

(Contd. of page 8)

· ADR, IMDG	Void
· UN proper shipping name	
· DOT	CONSUMER COMMODITY, ORM-D Paint
· ADR	Void
· IMDG	CONSUMER COMMODITY, ORM-D Void
· IATA	PAINT
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
<hr/>	
· ADR, ADN, IMDG	
· Class	Void
· IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IATA	III
· ADR, IMDG	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· Remarks:	CERCLA/DOT RQ: 617gal./4786 lbs.
· ADR	
· Remarks:	Packaging <450L: exemption viscous substances according to 2.2.3.1.5 > 450 l: 3 F1, III

(Contd. on page 10)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Bilge Paint

(Contd. of page 9)

- IMDG
- Remarks: > 450 1: 3, III
- UN "Model Regulation": Void

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

136-52-7	cobalt bis(2-ethylhexanoate)
112-34-5	2-(2-butoxyethoxy)ethanol

· TSCA (Toxic Substances Control Act):

64742-48-9	Naphtha (petroleum), hydrotreated heavy (Note-p)	ACTIVE
13463-67-7	titanium dioxide	ACTIVE
16389-88-1	dolomite	ACTIVE
14807-96-6	Talc (Mg3H2(SiO3)4)	ACTIVE
34590-94-8	Dipropylene glycol monomethyl ether	ACTIVE
8002-43-5	Soyalecithine	ACTIVE
68953-58-2	Ditallowdimethylammonium	ACTIVE
100-64-1	cyclohexanone oxime	ACTIVE
105-44-2	4-methylpentan-2-one oxime	ACTIVE
22464-99-9	Zirconiumoctoate, 12 % Zr	ACTIVE
68409-80-3	Isomers of fatty acid calcium salts, C6-C19	ACTIVE
7631-86-9	silicon dioxide, chemically prepared	ACTIVE
136-52-7	cobalt bis(2-ethylhexanoate)	ACTIVE
112-34-5	2-(2-butoxyethoxy)ethanol	ACTIVE
14808-60-7	Quartz (SiO2)	ACTIVE

· Hazardous Air Pollutants

136-52-7	cobalt bis(2-ethylhexanoate)
----------	------------------------------

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO2)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Bilge Paint

(Contd. of page 10)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

13463-67-7	titanium dioxide	A4
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2

· MAK (German Maximum Workplace Concentration)

13463-67-7	titanium dioxide	3A
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	3B
14808-60-7	Quartz (SiO <sub>2</sub> )	1

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO <sub>2</sub> )

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labeling:

Naphtha (petroleum), hydrotreated heavy (Note-p)

· Hazard statements

H226 Flammable liquid and vapor.  
H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 12)

Safety Data Sheet  
acc. to OSHA HCS

Printing date 01/12/2021

Reviewed on 01/12/2021

Trade name: Epifanes Bilge Paint

(Contd. of page 11)

- National regulations:
- Technical instructions (air):

Class	Share in %
NK	25-50

- Water hazard class:  
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection department.
- Contact: J.J. van Dijk
- Date of preparation / last revision 01/12/2021 / 2
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids - Category 3

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

- \* Data compared to the previous version altered.

None