

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

1 Identification

- Product identifier
- Trade name: Epifanes Poly-urethane Primer
- Application of the substance / the mixture
See our technical datasheet for application of this product.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31 297-360666
fax.+31 297-342078
email:info@epifanes.nl
- Information department: Research & Development.
- Emergency telephone number:
Emergency Phone Number (24 hours) CHEMTREC (800-424-9300)
Outside US: 703-527-3887

2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- Label elements

- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS02



GHS07



GHS08

- Signal word Danger

(Contd. on page 2)



Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer




(Contd. of page 1)

- Hazard-determining components of labeling:
Solvent naphtha (petroleum), light arom. (Note-P)
Xylene
4-methylpentan-2-one
ethylbenzene
- Hazard statements
H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.
H335 May cause respiratory irritation.
- Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Classification system:
- NFPA ratings (scale 0 - 4)
 Health = 2
Fire = 3
Reactivity = 0
- HMIS-ratings (scale 0 - 4)
 Health = 2
Fire = 3
Reactivity = 0
- Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description:
Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
EINECS: 265-199-0	(Note-P)	
Index number: 649-356-00-4	<ul style="list-style-type: none">  Flam. Liq. 3, H226  Asp. Tox. 1, H304  STOT SE 3, H335-H336 	

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 2)

CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4	4-methylpentan-2-one ----- ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351 ⚠ Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335	2.5-10%
CAS: 12001-26-2 EC number: 601-648-2	Mica	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7	Xylene ----- ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	2.5-10%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3	butanone ----- ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	≤2.5%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene ----- ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	≤2.5%
CAS: 3648-18-8	dioctyltin dilaurate ----- ⚠ Repr. 2, H361; STOT SE 2, H371; STOT RE 2, H373	<0.3%

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 3)

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

· PAC-1:

108-10-1	4-methylpentan-2-one	75 ppm
12001-26-2	Mica	9 mg/m ³
78-93-3	butanone	200 ppm
100-41-4	ethylbenzene	33 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
123-86-4	n-butyl acetate	5 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
78-92-2	butanol	150 ppm

· PAC-2:

108-10-1	4-methylpentan-2-one	500 ppm
12001-26-2	Mica	99 mg/m ³
78-93-3	butanone	2700* ppm
100-41-4	ethylbenzene	1100* ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 4)

7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
78-92-2	butanol	220 ppm
· PAC-3:		
108-10-1	4-methylpentan-2-one	3000* ppm
12001-26-2	Mica	590 mg/m ³
78-93-3	butanone	4000* ppm
100-41-4	ethylbenzene	1800* ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
123-86-4	n-butyl acetate	3000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
78-92-2	butanol	10000** ppm

7 Handling and storage

- Handling:
 - Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
 - Information about protection against explosions and fires:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
 - Conditions for safe storage, including any incompatibilities
 - Storage:
 - Requirements to be met by storerooms and receptacles: Store in a cool location.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
 - Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems:
No further data; see item 7.
- Control parameters
- Components with limit values that require monitoring at the workplace:
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 5)

108-10-1 4-methylpentan-2-one

PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI

12001-26-2 Mica

PEL	Long-term value: 20 mppcf ppm <1% crystalline silica
REL	Long-term value: 3* mg/m ³ *respirable dust; containing < 1% quartz
TLV	Long-term value: 3* NIC-0.1** mg/m ³ *resp.fraction;**no asbestos,<1%crystalline silica

1330-20-7 Xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

78-93-3 butanone

PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

108-10-1 4-methylpentan-2-one

PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI

12001-26-2 Mica

PEL	Long-term value: 20 mppcf ppm <1% crystalline silica
-----	---

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 6)

REL	Long-term value: 3* mg/m ³ *respirable dust; containing < 1% quartz
TLV	Long-term value: 3* NIC-0.1** mg/m ³ *resp.fraction;**no asbestos,<1%crystalline silica
1330-20-7 Xylene	
REL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
78-93-3 butanone	
REL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI
100-41-4 ethylbenzene	
REL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

· Regulatory information

- PEL: Guide to Occupational Exposure Values (OSHA PELs)
- REL: Guide to Occupational Exposure Values (NIOSH RELs)
- TLV: Guide to Occupational Exposure Values (TLV)

· Ingredients with biological limit values:

108-10-1 4-methylpentan-2-one	
BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
78-93-3 butanone	
BEI	2 mg/L Medium: urine Time: end of shift Parameter: MEK

(Contd. on page 8)

Safety Data Sheet
 acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 7)

100-41-4 ethylbenzene

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

- Additional information:
 The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes.
 Avoid contact with the eyes and skin.
- Breathing equipment:
 Suitable respiratory protective device recommended.
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
 Filter AX
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 8)

- For the permanent contact gloves made of the following materials are suitable:
Butyl rubber, glove thickness 0.7 mm, > 480 min breakthrough time / permeation to EN374.
- As protection from splashes gloves made of the following materials are suitable:
Nitrile
Glove thickness > 0.45 mm, breakthrough time > 30 min. to EN374
- Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- General Information
- Appearance:

Form:	Fluid
Color:	According to product specification
- Odor: Characteristic
- Odor threshold: Not determined.
- pH-value: Not determined.
- Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	>100 °C (>212 °F)
- Flash point: 16 °C (60.8 °F)
- Flammability (solid, gaseous): Not applicable.
- Ignition temperature: 460 °C (860 °F)
- Decomposition temperature: Not determined.
- Auto igniting: Product is not selfigniting.
- Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- Explosion limits:

Lower:	Not determined.
Upper:	Not determined.
- Vapor pressure: Not determined.
- Density at 20 °C (68 °F): 1.6 g/cm³ (13.352 lbs/gal)
- Relative density: Not determined.
- Vapor density: Not determined.
- Evaporation rate: Not determined.

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 9)

· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	40 s (ISO 6 mm)
· Solvent content:	
Organic solvents:	28.0 %
VOC content:	28.04 %
	VOC content: 448.6 g/l / 3.74 lb/gal
Solids content:	75.6 %
· Other information	No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:		
64742-95-6 Solvent naphtha (petroleum), light arom. (Note-P)		
Oral	LD50	3592 mg/kg (rat)
Dermal	LD50 (Konijn)	3160 mg/kg (rabbit)
Inhalative	LC50 (rat)	>6193 mg/m ³ (rat)
108-10-1 4-methylpentan-2-one		
Oral	LD50	2080 mg/kg bw (rat)
Dermal	LD50	16000 mg/kg bw (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)
78-93-3 butanone		
Oral	LD50	3300 mg/kg bw (rat)
Dermal	LD50	5000 mg/kg bw (rabbit)

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 10)

100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg bw (rat)
Dermal	LD50	17800 mg/kg bw (rabbit)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
14807-96-6	Talc (Mg3H2(SiO3)4)	3
108-10-1	4-methylpentan-2-one	2B
100-41-4	ethylbenzene	2B
7631-86-9	silicon dioxide, chemically prepared	3

- NTP (National Toxicology Program)
None of the ingredients is listed.
- OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- Recommendation:
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021




Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 11)

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name	
· DOT	CONSUMER COMMODITY, ORM-D Paint
· ADR	1263 PAINT
· IMDG	CONSUMER COMMODITY, ORM-D PAINT
· IATA	PAINT
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· ADR	
	
· Class	3 (F1) Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	-
· EMS Number:	F-E, S-E

(Contd. on page 13)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 12)

· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· Remarks:	CERCLA/DOT RQ: 617gal./4786 lbs.
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):	None of the ingredient is listed.	
· Section 313 (Specific toxic chemical listings):		
108-10-1	4-methylpentan-2-one	
100-41-4	ethylbenzene	
78-92-2	butanol	
· TSCA (Toxic Substances Control Act):		
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom. (Note-P)	ACTIVE
108-10-1	4-methylpentan-2-one	ACTIVE
1330-20-7	Xylene	ACTIVE
78-93-3	butanone	ACTIVE
25086-48-0	Azijnzure ethenylester, polymeer met chlooretheen en ethenol. Acetic acid ethenylester, polymer with chlorethene and ethanol.	ACTIVE

(Contd. on page 14)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 13)

100-41-4	ethylbenzene	ACTIVE
68611-44-9	Silicium hydrophobised high dispersion	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE
7631-86-9	silicon dioxide, chemically prepared	ACTIVE
3648-18-8	dioctyltin dilaurate	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
78-92-2	butanol	ACTIVE

· Hazardous Air Pollutants

108-10-1	4-methylpentan-2-one
1330-20-7	Xylene
100-41-4	ethylbenzene

· Proposition 65

· Chemicals known to cause cancer:

108-10-1	4-methylpentan-2-one
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-10-1	4-methylpentan-2-one
----------	----------------------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

108-10-1	4-methylpentan-2-one	I
78-93-3	butanone	I
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value)

14807-96-6	Talc (Mg3H2(SiO3)4)	A4
100-41-4	ethylbenzene	A3

· MAK (German Maximum Workplace Concentration)

14807-96-6	Talc (Mg3H2(SiO3)4)	3B
100-41-4	ethylbenzene	3A

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 15)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 14)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

- Hazard-determining components of labeling:
Solvent naphtha (petroleum), light arom. (Note-P)
Xylene
4-methylpentan-2-one
ethylbenzene

· Hazard statements

- H225 Highly flammable liquid and vapor.
- H319 Causes serious eye irritation.
- H361 Suspected of damaging fertility or the unborn child.
- H335 May cause respiratory irritation.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	25-50

· Water hazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

· Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Environment protection department.
- Contact: J.J. van Dijk
- Date of preparation / last revision 02/16/2021 / 2

(Contd. on page 16)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/16/2021

Reviewed on 02/16/2021

Trade name: Epifanes Poly-urethane Primer

(Contd. of page 15)

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids - Category 2
Flam. Liq. 3: Flammable liquids - Category 3
Acute Tox. 4: Acute toxicity - Category 4
Skin Irrit. 2: Skin corrosion/irritation - Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A
Carc. 2: Carcinogenicity - Category 2
Repr. 2: Reproductive toxicity - Category 2
STOT SE 2: Specific target organ toxicity (single exposure) - Category 2
STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2
Asp. Tox. 1: Aspiration hazard - Category 1

· * Data compared to the previous version altered.