

Schuller Eh'klar GmbH
AUSTRIA
 Im Astenfeld 6
 A – 4490 St. Florian
 Tel.(0043) 07224/68 200
 Fax(0043) 07224/68 282
 E-Mail: office@schuller.eu
 www.schuller.eu



01.08.2016

DUCT TAPE “X-Way”

(Articlenumbers: 45768, 45769)

Short description:

Standard ducttape for the construction sector. A high quality tape with a soft, synthetic rubber adhesive and good resistance against aging and temperature. As the backing serves a strong, weatherproof and waterproof coated, handtearable, polyester fabric. This tape is characterized by a very strong initial tack, good adhesion and excellent adhesion in the freezing point.

Product data:

Backing	LDPE-film + Polyester fabric
Adhesive	Synthetic rubber (solventfree)
Mesh	26
Total thickness	0,195 mm
Adhesion to steel	24 N/25mm
Tensile strenght	95 N/25mm
Rolling ball tack	<3 cm
Application temperature	-10°C - +75°C

Application:

This tape sticks perfectly on smooth and rough surfaces such as stone, concrete, wood and plastic and is for professional work indoors and outdoors.

Conditions:

Store in a cool and dry place, away from sunlight and direct heat. As far as the storage conditions are respected, the product is garanted 12 months.